

D4LED

Architektur

NEW!



4" LED Downlights

Four (4) 3-Watt white LEDs

Features

- Provides superior brightness control
- Equipped with (4) 3-Watt white high quality LEDs
- Integral heat sink provides 70% average lumen maintenance at 50,000 hours
- Advance Xitanium Electronic Driver
- CSA C/US listed suitable for wet location under covered ceiling

Order housing and housing options, reflector and reflector options, and accessories as separate line items. See ordering example below.

Catalog No. Description

Line 1 Order Housing and Housing Options:

Housings

D4LED 4" LED downlight housing

Housing Options

277V J-Box mounted step-down transformer

Line 2 Order Light Engine and Light Engine Options:

Reflectors (Refer to page 219 for descriptions and available reflector finishes)

4D9 4" Open Reflector/Light Engine Assembly w/ (4) 3W white LEDs

Reflector Finish

Blank Specular Alzak

SS Semi-Specular Alzak

MFC American Matte™ Alzak

Reflector Color

Blank Clear Alzak

CG Champagne Gold Alzak

WE Wheat Alzak

LW Light Wheat Alzak

PW Pewter Alzak

BL Black Alzak

WH White Paint

Reflector Options

TRG Trim ring gasket (factory installed)


WT Painted white trim

Line 3 Order Accessories:

B24 Set of two (2) 24" bar hangers for T-bar ceilings

B6 Set of two (2) bar hangers for ceiling joists up to 24" centers

SCA5 Sloped ceiling adapter for 4" housing (specify degree of slope and type of ceiling.) Not recommended for wall wash applications. Sloped ceiling adapter and housings must be installed into the ceiling structure at the same time.




Line 1
Line 2
Line 3

Ordering Example:

D4LED

4D9

B24



Maximum ceiling thickness = 1 1/4"
Ceiling Cutout = 5 3/8"